



SAVE
UP TO
30%
ON INSTALLATION TIME

PROTECTION FELT FOR LINERS

COVER' LINER

SPECIAL Renovation



Slightly fibrous
surface in contact
with concrete, wood
or metal.

Colour : 1975 Pale Grey

Smooth surface in
contact with liner

Liner Cover'Liner Renov Concrete



EFFICIENT PROTECTIVE BARRIER (walls and bottom) between foundations and liner

- Shock absorption
- Protects against perforation: thickness and density fibres protect from any sharp elements
- Hides any imperfections of concrete walls

CONSTRUCTION SITE AESTHETICS

Beautiful seamless felt visually more aesthetic than welded foam tiles, clean and well-renovated site.



ENVIRONMENTALLY FRIENDLY

- Manufactured with thermofusion fibres (low energy consumption)
- No chemicals binders or latex
- Eco-designed and recyclable felt

INERT MATERIAL / ROT-PROOF



EASY TO INSTALL

- Very easy to cut
- water-resistant binding agent to provide rigidity and flexibility to the felt
- Light flecked grey colour avoiding light reflection
- Edge-to-edge installation



TECHNICAL DATA

Surface: needlepunched homogeneous felt

Fibres: 100 % polypropylene, naturally resistant to wet environments

Backing: impregnated

Thickness: 4,3 ± 0,3mm

Total weight: 750 g/m² ± 10%

Ø roll: 41 cm

Ø tube: 100 mm

INSTALLATION

Clean the concrete to remove all the dust.

Smooth surface: liner side

Slightly fibrous surface: concrete, wood or metal side

Glue with a spray glue.

1,5 x 30 m STRIW1975G150

2 x 30 m STRIW1975C2

Sold in europalette of 6 rolls vertically stored

SOMMER
TECHNICAL

A Sommer Needlepunch brand

Sommer Needlepunch
341, rue de la Mairie
59780 Baisieux - France

Contact:
coverliner@sommernp.com
www.sommernp.com

Linerenov 2025-A1-0225 / Photo credit : Sommer.
We reserve the right to alter technical specifications without prior notice.

