


PROTECTION FELT FOR LINERS

COVER' LINER

Premium

Slightly fibrous surface in contact with concrete, wood or metal.







EFFICIENT PROTECTIVE BARRIER

(walls and bottom) between foundations and liner

- Shock absorption
- Protects against perforation: thickness and density fibres protect from any sharp elements
- · Hides any imperfections of concrete walls



ENVIRONMENTALLY FRIENDLY

- Manufactured with thermofusion fibres (low energy consumption)
- No chemicals binders or latex
- · Eco-designed and recyclable felt

INERT MATERIAL / ROT-PROOF



ANTI-BACTERIAL FELT

- anti-bacterial (no pink stain according to ASTM E 1428)
- anti-fungal (according to EN ISO 846 Section A)
- anti-algae (according to SAN BIO 33/99)
 Test on request.



EASY INSTALLATION

- Easy to cut
- Bright flecked grey avoiding light reflection
- Edge-to-edge installation







TECHNICAL DATA

Surface

needlepunched homogeneous felt containing a biocide product (substance active Thiabendazole / N-Butyl-benzisothizolinone)

Fibres: 100 % polyolefin, naturally resistant to wet environments and treated Sanitized®

Backing: thermofusion fibres

Thickness: 2.7 ± 0.3 mm

Total weight: $350 \text{ g/m}^2 \pm 10\%$

Ø roll: 35 cm

Ø tube: 100 mm

INSTALLATION

Clean the concrete to remove all the dust Smooth surface: towards liner Slightly fibrous surface: concrete,wood or metal side Glue with a spray glue.

1,5 x 30 m PMMTF1985G150

2 x 30 m PMMTF1985C2

On order with 5000 m² minimum Sold in europalette of 8 rolls vertically stored



Sommer Needlepunch 341, rue de la Mairie 59780 Baisieux - France Contact: coverliner@sommernp.com www.sommernp.com

